

雙錘打擊式 Double Hammer



NR-5S (下壓啟動式 Push-to start)



NR-5SL (板機啟動式 Lever-operated)



NR-5SA



NR-6SSLD



NR-6SLD



NR-5SP

型號 Model	能力 Capacity		扭力範圍 Torque about		轉數 Free-speed r.p.m.	重量 Weight		長度 Length		外徑 dia		入氣頭 Air Inlet	氣管 Air Hose	空氣壓力 Air Pressure
	mm	mm	mm	mm		lb	kgs	in	mm	in	mm			
NR-5S	4-5		6.9-13		10000	1.8	0.8	8-1/8	207	1-1/8	40	PT1/4	1/4	6kg/cm ²
NR-5SL	4-5		6.9-13		10000	1.8	0.8	8-1/4	215	1-1/8	40	PT1/4	1/4	6kg/cm ²
NR-5SA	4-5		6.9-13		10000	2.4	1.1	10	255	1-1/8	40	PT1/4	1/4	6kg/cm ²
NR-5SP	4-5		6.9-13		10000	2.1	0.9	6-1/4	160	1-1/8	40	PT1/4	1/4	6kg/cm ²
NR-6SSLD	6		9.8-18		8000	2.2	1	8	202	1-7/8	44	PT1/4	1/4	6kg/cm ²
NR-6SLD	6		9.8-18		8000	2.4	1.2	7	175	1-7/8	44	PT1/4	1/4	6kg/cm ²

滑動式離合器 Cushion-Clutch Type



NR-3.5A (bit he x 5m/m)
NR-3.5B (bit he x 6.35m/m)



NR-4 (bit he x 5m/m)



NR-5 (bit he x 6.35m/m)

型號 Model	能力 Capacity		扭力範圍 Torque about		轉數 Free-speed r.p.m.	重量 Weight		長度 Length		外徑 dia		入氣頭 Air Inlet	氣管 Air Hose	空氣壓力 Air Pressure
	mm	mm	mm	mm		lb	kgs	in	mm	in	mm			
NR-3.5(A,B)	3-4		1.2-2.5		2000	1.2	0.6	8	196	1-3/8	34	PT1/4	1/4	5kg/cm ²
NR-4	4-5		2.3-4.4		1400	2.2	1	9-1/4	236	1-1/2	40	PT1/4	1/4	5kg/cm ²
NR-5	5-6		3.4-7.8		1400	2.3	1.1	10-1/2	258	1-1/2	40	PT1/4	1/4	5kg/cm ²

滑動式離合器 — 內強力磁鐵裝置 Cushion-Clutch Type (Magnetic)



NR-3.5MA (bot he x 6.35m/m)



NR-4MA (bot he x 6.35m/m)



NR-5MA (bot he x 6.35m/m)

型號 Model	能力 Capacity		扭力範圍 Torque about		轉數 Free-speed r.p.m.	重量 Weight		長度 Length		外徑 dia		入氣頭 Air Inlet	氣管 Air Hose	空氣壓力 Air Pressure
	mm	mm	mm	mm		lb	kgs	in	mm	in	mm			
NR-3.5MA	3-4		1.2-2.5		2000	1.2	0.6	8	196	1-3/8	34	PT1/4	1/4	5kg/cm ²
NR-4MA	4-5		2.3-4.4		1400	2.2	1	9-1/4	240	1-1/2	40	PT1/4	1/4	5kg/cm ²
NR-5MA	5-6		3.4-7.8		1400	2.3	1.1	10-1/4	250	1-1/2	40	PT1/4	1/4	5kg/cm ²

自動停止式離合器 Air-Shut-Off Type



NR-ST14 Series (A TYPE bit hex 5m/m)
NR-C14 Series Series



NR-ST22 Series (bit he x 6.35m/m)
NR-C22 Series Series



NR-ST0511 NR-C0515 (bit he x 6.35m/m)

型號 Model	扭力範圍 Torque about			轉數 Free-speed r.p.m.	重量 Weight		長度 Length		外徑 dia		入氣頭 Air Inlet	氣管 Air Hose	空氣壓力 Air Pressure
	mm	kg-cm	in-lb		lb	kgs	in	mm	in	mm			
NR-ST0511	0.05-0.58	0.5-6	0.43-5.2	1100	0.5	0.25	8	203	7/8	23	PT1/8	1/4	5kg/cm ²
NR-ST1011	0.2-0.7	2.5-7	2-6	1100	0.6	0.3	8	203	7/8	23	PT1/8	1/4	5kg/cm ²
NR-ST1015	0.4-1	4-10	3.5-8.7	1500	0.6	0.3	8	203	7/8	23	PT1/8	1/4	5kg/cm ²
NR-ST1416	0.7-1.3	7-13	6-11.3	1600	1.3	0.6	8-1/2	216	1-1/8	28.5	PT1/8	1/4	5kg/cm ²
NR-ST1409	1.1-2	11-20	9.6-17	900	1.3	0.6	8-1/2	216	1-1/8	28.5	PT1/8	1/4	5kg/cm ²
NR-ST1817	1-3	10-30	8.5-26	1700	1.8	0.8	9-3/8	238	1-3/8	34.5	PT1/4	3/8	6kg/cm ²
NR-ST1811	1.5-3.5	15-35	13-30	1100	1.8	0.8	9-3/8	238	1-3/8	34.5	PT1/4	3/8	6kg/cm ²
NR-ST1807	1.5-4	15-40	13-34.5	700	1.8	0.8	9-3/8	238	1-3/8	34.5	PT1/4	3/8	6kg/cm ²
NR-ST2212	2-4.4	20-45	17-39	1200	2.5	1.1	10-1/2	267	1-1/2	40	PT1/4	3/8	6kg/cm ²
NR-ST2208	3-6	30-60	26-52	800	2.5	1.1	10-1/2	267	1-1/2	40	PT1/4	3/8	6kg/cm ²
NR-ST2205	3-7	30-70	26-60.8	500	2.5	1.1	10-1/2	267	1-1/2	40	PT1/4	3/8	6kg/cm ²