

UPT (URYU Pneumatic Tools)

3/4"-1" CAPACITY IMPACT WRENCHES (REVERSIBLE)

**UW-220P SERIES, 3/4" CAPACITY, TORQUE RANGE : 30~70 KG.M
210~510 FT.LBS**

**UW-251P SERIES, 3/4"-1" CAPACITY, TORQUE RANGE : 60~100 KG.M
420~720 FT.LBS**



**MODEL
UW-220P**

- UW-220P
(Short Anvil)
- UW-220PL
(Long Anvil)
- SOCKET RETAINING METHOD
Friction Ring Type, O Ring Type

- * Well-balanced impact mechanism
- * Reliable, powerful, efficient operation
- * Thick rubber bumper for hammer casing protection
- * Tough sandcast housings for greater durability
- * Three piece construction for easy maintenance
- * Four position built-in power regulator

Featured with URYU unique Swing Hammer Mechanism, UW-220P and UW-251P series Impact Wrenches are ideal for heavy industrial production work.



**MODEL
UW-251P**

- UW-251P
(Short Anvil)
- UW-251PL
(Long Anvil)
- 3/4" SQ Anvil available as option

SPECIFICATIONS

Recommended Air Pressure : 0.6MPa (85psi)

Model	Capacity (Bolt Size)		Free Speed (about)	Overall Length (about)		Weight less Socket (about)		From Center to Outside (about)		SQ Drive Shank		Air Inlet Thread (Pipe Tap)	Air Hose Size		Average Air Consumption (about)	
	in	mm	r.p.m.	in	mm	lb	kg	in	mm	in	mm	in	in	mm	ft ³ /min.	m ³ /min.
UW-220P	3/4	19	5,500	8 7/8	225	9.6	4.4	1 3/32	42	3/4	19	N.P.T. 3/8	1/2	12.7	25	0.7
UW-220PL	3/4	19	5,500	13 1/4	338	10.3	4.7	1 3/32	42	3/4	19	N.P.T. 3/8	1/2	12.7	25	0.7
UW-251P	1	25	5,500	10 53/64	275	17.6	8.0	1 7/8	48	1	25.4	N.P.T. 3/8	1/2	12.7	28	0.8
UW-251PL	1	25	5,500	15 33/64	394	19.4	8.8	1 7/8	48	1	25.4	N.P.T. 3/8	1/2	12.7	28	0.8

