

UPT (URYU Pneumatic Tools)

Direct-Drive SCREW DRIVERS (40 & 50 Series)

URYU offer now LD-series Direct-Drive Screwdrivers, which feature :

- 1/4" Hex. quick-change chuck.
- Handle exhaust for quiet operation.
- One hand reversible operation.
- Three (3) speeds are available for each series.

MODEL
US-LD40P-15

MODEL
US-LD50P-08

QUICK
CHANGE
CHUCK

THROTTLE
BUTTON

REVERSING
SWITCH

REVERSING SWITCH

Can be installed either left or right for convenience of the operator.

UP for
reversing



DOWN for
forwarding

UP for
forwarding



DOWN for
reversing

AIR INLET

EXHAUST
DEFLECTOR
(SILENCER)

SPECIFICATIONS (Subject to change without notice)

Recommended Air Pressure : 0.5Mpa(71psi)

Model	Capacity (Screw Size)		Torque Range				Overall Length (about)		Weight Less Bit (about)		From Center to Outside (about)		Bit Shank		Free Speed (about)	Average Air Consumption	
	mm	in	ft-lbs	Nm	ft-lbs	Nm	mm	in	kg	lb	mm	in	mm	in	rpm	m³/min.	ft³/min.
US-LD40P-08	M5	3/16	3.6	4.8	4.2	5.7	130	5 1/4	0.7	1.54	17	43/64	6.35	1/4	940	0.4	14.0
US-LD40P-15	M4	5/32	2.2	3.0	2.4	3.2	130	5 1/4	0.7	1.54	17	43/64	6.35	1/4	1,700	0.4	14.0
US-LD40P-21	M4	5/32	1.5	2.0	2.1	2.8	130	5 1/4	0.7	1.54	17	43/64	6.35	1/4	2,500	0.4	14.0
US-LD50P-05	M5	3/16	7.4	10.0	8.3	11.2	153	6 1/32	0.9	2.01	20	49/64	6.35	1/4	500	0.5	17.5
US-LD50P-08	M5	3/16	4.8	6.5	5.8	7.8	153	6 1/32	0.9	2.01	20	49/64	6.35	1/4	900	0.5	17.5
US-LD50P-17	M4	5/32	2.6	3.5	4.4	5.9	150	5 29/32	0.9	2.01	20	49/64	6.35	1/4	1,900	0.5	17.5

Standard Accessories : Air Hose Nipple, Bit.
Air Inlet Thread : NPT1/4, Air Hose Size : 6.35mm(1/4")



URYU SEISAKU, LTD.

Osaka, Japan

OKA-270-11-06-23-2019

Oct 2011