

Specifications UAN-611R & UAN-701R Series

Recommended Air Pressure : 0.6MPa (85psi)



Model	Bolt Capacity		Max. Torque		Free Speed (about)	Overall Length (about)		Weight less Socket (about)		From Center to Outside (about)		Angle Height (about)		Square Drive Shank		Average Air Consumption		Noise Level	Vibration Level
	mm	in	Nm	ft-lbs	r.p.m.	mm	in	kg	lb	mm	in	mm	in	mm	in	m³/min	ft³/min	dB(A)	m/sec²
UAN-611R-60C	6	1/4	6.5-12.0	4.3-8.6	620	383	15 5/64	1.6	3.52	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-611R-50C	6-8	1/4-5/16	8.5-15.0	5.7-10.8	470	373	14 11/16	1.6	3.52	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-611R-40C	6-8	1/4-5/16	10.0-18.0	7.2-12.9	400	373	14 11/17	1.6	3.52	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-611R-30C	8	5/16	13.0-25.0	9.3-18.0	270	373	14 11/18	1.6	3.52	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-701R-60C	8	5/16	20.0-31.0	14.5-23.1	600	445	17 33/64	2.4	5.29	21.5	27/32	47	1 55/64	9.5	3/8	0.9	31.8	85	1.78
UAN-701R-40C	8-10	5/16-3/8	28.0-45.0	21.0-33.3	400	455	17 29/32	2.4	5.29	21.5	27/32	51	2	9.5	3/8	0.9	31.8	85	1.78
UAN-701R-30C	10-12	3/8-1/2	37.0-60.0	27.5-44.1	300	455	17 29/32	2.4	5.29	21.5	27/32	58	2 9/32	12.7	1/2	0.9	31.8	85	1.78

Air Inlet Thread (Pipe Tap) : N.P.T. 1/4"
Air Hose Size (Inside Diameter) : 9.5mm (3/8")



Model	Bolt Capacity		Max. Torque		Free Speed (about)	Overall Length less Socket (about)		Weight less Socket or t (about)		From Center to Outside (about)		Angle Height (about)		Square Drive Shank		Average Air Consumption		Noise Level	Vibration Level
	mm	in	Nm	ft-lbs	r.p.m.	mm	in	kg	lb	mm	in	mm	in	mm	in	m³/min	ft³/min	dB(A)	m/sec²
UAN-611RM-60C	6	1/4	6.5-12.0	4.3-8.6	620	419	16 1/2	2.0	4.4	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-611RM-50C	6-8	1/4-5/16	8.5-15.0	5.7-10.8	470	409	16 7/64	2.0	4.4	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-611RM-40C	6-8	1/4-5/16	10.0-18.0	7.2-12.9	400	409	16 7/64	2.0	4.4	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-611RM-30C	8	5/16	13.0-25.0	9.3-18.0	270	409	16 7/64	2.0	4.4	14.0	35/64	47	1 55/64	9.5	3/8	0.6	21.2	80	1.78
UAN-701RM-60C	8	5/16	20.0-31.0	14.5-23.1	600	480	18 57/64	2.7	5.94	21.5	27/32	47	1 55/64	9.5	3/8	0.9	31.8	85	1.78
UAN-701RM-40C	8-10	5/16-3/8	28.0-45.0	21.0-33.3	400	492	19 3/8	2.9	6.38	21.5	27/32	51	2	9.5	3/8	0.9	31.8	85	1.78
UAN-701RM-30C	10-12	3/8-1/2	37.0-60.0	27.5-44.1	300	492	19 3/8	2.9	6.38	21.5	27/32	58	2 9/32	12.7	1/2	0.9	31.8	85	1.78

Air Inlet Thread (Pipe Tap) : N.P.T. 1/4"
Air Hose Size (Inside Diameter) : 9.5mm (3/8")



UPT URYU PNEUMATIC TOOLS



Torque Control

Angle Nutrunners

Recommended Torque Range : 6.5Nm ~ 60.0Nm (Clutch type, Reversible)

UAN-611R-60C / UAN-611R-50C / UAN-611R-40C / UAN-611R-30C
UAN-701R-60C / UAN-701R-40C / UAN-701R-30C

New and improved
Six Performance Advantages.

URYU SEISAKU,LTD.

P.O. Box 7, Higashinari, Osaka, Japan.
Telephone No : 06-6973-9414-9415
Fax : 06-6972-0346
E-Mail : uryuair@uryu.co.jp



Distributed by

DAI-002-020420-2003

URYU SEISAKU,LTD.
Osaka,Japan

